

Product: Texoflex AL



Texoflex AL is made of single layer corrugated aluminium AL 99,5 resistant to moisture. Due to transport and dimensional stability the duct can be compressed to approx. 1/3 of its length.

Application:

Texoflex AL Stretch is designed for the installation into the existing or new ventilation systems and ventilation of wet environments.

Product construction:

The product Flexible duct „Texoflex AL “ include the following components:

- 1 Layer of Aluminium

Properties:

Good flexibility
Good compression

Specification:

Product code: given in the table bellow,
Temperature range: from -30° C to +200° C,
Diameters: from 80 mm to 356 mm,
Standard length: 3 m

Table: Ordering information

Product code Tehnoexport	Product name Klima oprema	Dia.	Length	Box dimension	Pallete dimension	Pcs per box	Boxes per pallet
		mm	m	mm	cm		
TALS100/3	Texoflex AL Stretch - dia. 100 mm x 3,0 m	100	3	130x130x1000	100x120	1	153
TALS110/3	Texoflex AL Stretch - dia. 110 mm x 3,0 m	110	3	130x130x1000	100x120	1	153
TALS120/3	Texoflex AL Stretch - dia. 120 mm x 3,0 m	120	3	130x130x1000	100x120	1	153
TALS130/3	Texoflex AL Stretch - dia. 130 mm x 3,0 m	130	3	160x160x1000	100x120	1	98

Packaging information: Box color - Brown

L = the position of the label in the upper left corner, straight to the edges



Label: White color, 70x90mm

